

4/8

- Port Checking Pattern Matching Monitor (PCPMM)
- a. Parameters for monitor provisioning:
 - i. Input: ip_address, port, retries, timeout, cycle time
 - ii. Output: none
 - b. Parameters for monitor de-provisioning:
 - i. Input: port
 - ii. Output: none

FIG. 5A

- MQ Monitor PAC (ITMMQ)
- a. Parameters for monitor provisioning:
 - i. Input: endpoint_label, definition_filename
 - ii. Output: MQ_management_domain, profile_manager_label, MQ_Tmwk2Profile_name, MQ_Qmgr_object
 - b. Parameters for monitor de-provisioning:
 - i. Input: MQ_management_domain, profile_manager_label, MQ_Tmwk2Profile_name, MQ_Qmgr_object
 - ii. Output: none

FIG. 5B

- Websphere Monitor PAC (ITMWS)
- a. Parameters for monitor provisioning:
 - i. Input: endpoint_label, nodename, fully_quality_host_name, itm_policy_region, os_type, admin_port_number, websphere_version, websphere_security_enabled, websphere_security_properties_file, websphere_install_path, app_server_name, has_web_module, has_ebj_module, adminserver_definition_filename, appserver_definition_filename, ws_fava_path
 - ii. Output: ws_policy_region, adminserver_profile_manager, appserver_profile_manager, adminserver_tmw2kprofile, appserver_tmw2kprofile, adminserver_object_label
 - b. Parameters for monitor de-provisioning:
 - i. Input: ws_policy_region, adminserver_profile_manager, appserver_profile_manager, adminserver_tmw2kprofile, appserver_tmw2kprofile, adminserver_object_label
 - ii. Output: none

FIG. 5C